

BEST AVAILABLE COPY

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
28 October 2004 (28.10.2004)

PCT

(10) International Publication Number
WO 2004/092473 A1

(51) International Patent Classification: D05B 97/12,
G01B 3/00

(21) International Application Number:
PCT/GB2004/001656

(22) International Filing Date: 15 April 2004 (15.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0308653.5 15 April 2003 (15.04.2003) GB

(71) Applicant (for all designated States except US): CRE-
ATIVE GRIDS UK LTD (GB/GB); 71 Westfield Road,
Leicester LE3 6HU (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): WATERFIELD, John
(GB/GB); Creative Grids UK Ltd, 71 Westfield Road, Le-
icester LE3 6HU (GB).

(74) Agents: STAGG, Diana, C. et al.; Marks & Clerk, 144
New Walk, Leicester LE1 7JA (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, GR, GU, HT, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MY, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SI, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: IMPROVED RULER AND METHOD OF MANUFACTURE

(57) Abstract: A process for the manufacture of a ruler for use in the accurate measuring of fabric for quilting, patchwork and other crafts includes the steps of forming a ruler blank from a single layer of a substantially transparent material, printing, in one or more discrete stages, a pattern onto a surface of the blank, the pattern comprising a single colour or multi-colour pattern corresponding to the scalar markings on the ruler and in a further stage printing a non-slip pattern onto the same surface of the ruler, characterised in that the printing composition used for printing the non-slip pattern comprises an ink which can be dried using ultra violet light; an adhesive and a granular filler, capable of imparting non-slip properties to the surface of the ruler. A ruler produced according to this process is also described.

WO 2004/092473 A1

JC20 Rec'd PCT/PTO 1 4 OCT 2005

Title: Improved Ruler and Method of Manufacture

The present invention relates to an improved ruler, in particular to an improved ruler of the type known as a quilting ruler, especially a clear acrylic quilting ruler, which rulers are for use in measuring fabric for quilting and related needlework, scrapbooking and other craft techniques. Rulers of this type have a lower, fabric-
5 contacting, surface and an upper surface through which the scalar markings on the ruler can be viewed.

The present invention further relates to an improved process for the manufacture of rulers of this type and to rulers which have been manufactured using the improved
10 process.

It is known to produce rulers which have a pattern printed onto the lower, fabric-
contacting, surface. These patterns are printed onto the ruler after the scalar markings have been printed, using printing compositions which typically comprise an ink, in particular a screen printing ink; an adhesive; a varnish, for example an acrylic varnish
15 and a filler, in particular finely ground sand or pumice, dissolved in a solvent. When used to print an area onto a quilting ruler of the type described above, the printing imparts non-slip characteristics thereto.

It is a disadvantage of the printing compositions known for use in this process, that,
20 after the liquid printing composition has been applied in the desired pattern to an article, the article has to be transferred to a rack and allowed to dry in the air over a period of several hours, typically overnight. In the case of rulers, in particular quilting rulers, it is required that the rulers are additionally printed with one or more sets of scalar markings in different colours using inks without fillers. Where the article is to
25 be printed in this way, each set of coloured markings has to be allowed to dry, again over a period of several hours, which means that the manufacture of these articles takes an uneconomically long period of time. In addition, the printing process has to

be carried out as a batch process rather than a continuous process, which is less desirable.

It is a further disadvantage of the known process that, because the printing compositions used in the known process are solvent based, the solvent tends to
5 evaporate from the composition before the composition is applied to the substrate, so that solvent has to be added to the composition to maintain the required viscosity. It is a further disadvantage that because the composition is solvent based, it cannot be left in the screen during breaks in work because of the risk of the ink drying in the image area and damaging the screen. It is a still further disadvantage of solvent based
10 printing compositions that the use of solvents may cause environmental problems.

It is a further disadvantage of rulers printed according to the known process that, after extensive use, the non-slip character of the printed pattern degrades and may be reduced by as much as 75% of its original level due to wear and to scratching. It is
15 observed that while the printed marks are still visible, the filler has worn away or been scratched off.

It is also a disadvantage of rulers printed according to the known process that, in order to provide the non-slip area with sufficient 'grip' the fabric-contacting surface of the printed area may be undesirably rough, leading to snagging of the fabric, or may be excessively opaque, at least partially obscuring the fabric and/or the scalar
20 markings on the ruler.

It is an object of the present invention to provide an improved ruler and an improved process for its manufacture, in which the above disadvantages are reduced or substantially obviated.

The present invention provides a process for the manufacture of a ruler for use in the
25 accurate measuring of fabric for quilting, patchwork and other crafts, which process includes the steps of forming a ruler blank from a single layer of a substantially transparent material, printing, in one or more discrete stages, a pattern onto a surface

of the blank, the pattern comprising a single colour or multi-colour pattern corresponding to the scalar markings on the ruler and in a further stage printing a non-slip pattern onto the same surface of the ruler, characterised in that the printing composition used for printing the non-slip pattern comprises an ink which can be
5 dried using ultra violet light; an adhesive and a granular filler, capable of imparting non-slip properties to the surface of the ruler.

In a preferred embodiment of the process according to the invention, the printing composition further comprises a photo initiator.

Preferred granular fillers include glass beads, ground glass, pumice or ground plastics
10 materials.

The pattern printed onto the ruler to provide the scalar markings is preferably printed using a screen printing process using an ultraviolet printing ink.

The present invention further provides a ruler which has been printed by the process according to the invention.

15 It has surprisingly been found that rulers produced according to the present invention have increased resistance to wear, the non-slip properties being maintained over extended periods of use.

It has also surprisingly been found that, in rulers produced according to the present invention, the non-slip areas are smoother than those produced by the conventional
20 process, reducing the danger of snagging and are less opaque, improving the visibility in use of the scalar markings and the fabric.

In use, the non-slip areas of rulers produced according to the present invention provide excellent grip characteristics on a wide variety of fabrics, in particular the fabrics generally used in quilting, patchwork, needlework and crafts. The rulers can

also be used in paper and card crafts, when the non-slip[characteristics are also useful and effective.

The rulers according to the present invention are used accurately to measure pieces of fabric, in one or more layers, which are then cut to exact size with the ruler in place, generally using a rotary cutter. The pieces of fabric are then joined to other pieces of fabric to make a finished article. It will be appreciated that, for the accurate cutting of the pieces of fabric, which is essential for their future use, any slippage between the ruler and the fabric must be minimised.

The opaque, non-slip areas on the fabric-contacting surface of the transparent ruler allow the user to maintain the ruler in precise contact with the fabric, while at the same time enabling the user to see the ruler markings and the fabric clearly.

It is a further advantage of the process according to the invention, that the time taken to produce a ruler, in particular the drying time, is very much reduced. In conventional printing processes using a solvent based air drying printing compositions, the drying time is typically of the order of eight hours. In contrast to this, when the process according to the invention is used to manufacture a ruler, and the printed ruler is passed through a UV dryer, typically at a temperature not exceeding about 40° C, the ruler is dry within 30 seconds. The dried ruler can then be printed with further colours in the same way if required and can then be packaged ready for shipping.

Claims

1. A process for the manufacture of a ruler for use in the accurate measuring of fabric for quilting, patchwork and other crafts, which process includes the steps of forming a ruler blank from a single layer of a substantially transparent material, printing, in one or more discrete stages, a pattern onto a surface of the blank, the pattern comprising a single colour or multi-colour pattern corresponding to the scalar markings on the ruler and in a further stage printing a non-slip pattern onto the same surface of the ruler, characterised in that the printing composition used for printing the non-slip pattern comprises an ink which can be dried using ultra violet light; an adhesive and a granular filler, capable of imparting non-slip properties to the surface of the ruler.
2. A process according to claim 1 wherein the printing composition further comprises a photo initiator.
3. A process according to claim 1 or claim 2 wherein the granular filler comprises glass beads, ground glass, pumice or ground plastics materials.
4. A process according to any of claims 1 to 3 wherein the pattern printed onto the ruler to provide the scalar markings is printed using a screen printing process using an ultraviolet printing ink.
5. A ruler which has been printed by the process according to any of claims 1 to 4.
6. A ruler according to claim 5 which is a clear acrylic quilting ruler.

INTERNATIONAL SEARCH REPORT

Int. Application No.
PCT/GB2004/001656

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 005B97/12 601B3/00		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 005B A41H 601B C09D		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 02/29147 A (CREATIVE GRIDS UK LTD ; TANDY RACHEL CLAIRE (GB)) 11 April 2002 (2002-04-11) claims	1,5
A	WO 97/09179 A (SCHAFFER RANDAL D) 13 March 1997 (1997-03-13) page 3, line 7	1,5
A	US 2003/054121 A1 (THIEMANN RONALD) 20 March 2003 (2003-03-20) abstract	1,5
A	US 5 798 147 A (SCHUHMACHER PETER ET AL) 25 August 1998 (1998-08-25)	
A	US 6 321 458 B1 (HESS KATHERINE L) 27 November 2001 (2001-11-27)	
<input type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "Z" document member of the same patent family		
Date of the actual completion of the international search 16 August 2004		Date of mailing of the international search report 23/08/2004
Name and mailing address of the ISA European Patent Office, P.B. 5518 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3010		Authorized officer Debard, M

INTERNATIONAL SEARCH REPORT

International Application No.
PCT/GB2004/001656

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0229147	A	11-04-2002	AU 9009101 A	15-04-2002
			CA 2424674 A1	11-04-2002
			EP 1322809 A1	02-07-2003
			WO 0229147 A1	11-04-2002
			JP 2004510511 T	08-04-2004
			NO 20031524 A	03-04-2003
			NZ 524784 A	25-07-2003
			US 2004049935 A1	18-03-2004
WO 9709179	A	13-03-1997	AT 213466 T	15-03-2002
			AU 5714596 A	27-03-1997
			DE 69619387 D1	28-03-2002
			DE 69619387 T2	10-10-2002
			EP 0852542 A1	15-07-1998
			WO 9709179 A1	13-03-1997
US 2003054121	A1	20-03-2003	NONE	
US 5798147	A	25-08-1998	DE 4441651 A1	25-04-1996
			DE 19532419 A1	06-03-1997
			AT 178636 T	15-04-1999
			BR 9510303 A	11-11-1997
			CN 1166851 A	03-12-1997
			CZ 9701529 A3	17-06-1998
			DE 59505609 D1	12-05-1999
			WO 9602597 A2	01-02-1996
			EP 0793693 A2	10-09-1997
			ES 2130680 T3	01-07-1999
			JP 10508882 T	02-09-1998
US 6321458	B1	27-11-2001	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.